

Born, bred and here to stay. We were born in Michigan and bred on hitches and trailers all over North America. And we still manufacture our products in the heartland of the automotive world...Michigan USA. For 30 years, we've been designing and producing innovative products to make your adventures safe and secure with a simple philosophy: if we can't do it better, we don't do it. – Gary Johnson, President



Trailer Coupler Locks

- RC1 Adjustable Coupler Lock for lever-style coupler requiring a 5/8" to 23/8" span.
- RC2 Coupler Lock for lever-style coupler requiring a $1/2^{"}$ opening.
- RC3 Coupler Lock for lever-style coupler requiring a 2" opening (shown).
- RC4 Surge Brake Coupler Lock for coupler requiring a $2^{1}/2^{"}$ opening.
- RCS Surge Brake Coupler Lock for coupler requiring a 33/8" opening.
- RC6 Coupler Lock for lever-style coupler requiring a 7/8" opening.
- RC2-SS Stainless steel Coupler Lock for leverstyle coupler requiring a 1/2" opening
- RC6-SS Stainless steel Coupler Lock for leverstyle coupler requiring a 7/8" opening.
- TCL1-AS Trailer Coupler Lock. Fits 17/8" and 2"
- -YL lip-engaging, trigger-style couplers. Coupler should have flat lip around the bottom. Maximum lip width: 33/4"
- TCL2-AS Trailer Coupler Lock. Fits 2⁵/16" lip-engaging, trigger-style couplers. Coupler should have rolled lip around the bottom. Maximum lip width: 4¹/2"

TCL-3-AS Trailer Coupler Lock. Fits 25/16" -YL lip-engaging, trigger-style couplers.

Coupler should have flat lip around the bottom. Maximum lip width: 41/2



Receiver Hitch Locks

RH2-XL Hitch Lock with 1/2" dia. pin for 11/4" x 11/4" Class 2 receiver. RH3 Hitch Lock with 5/8" dia. pin for 2" x 2" Class 3, 4 receiver (shown).

- RH5-XL Hitch Lock with $\frac{5}{8}$ dia. pin for $2^{1}/2^{"} \times 2^{1}/2^{"}$ receiver (Class 5) or $3\frac{5}{8}$ span.
- RH3-SS Solid stainless steel Hitch Lock with 5/8" dia. pin for 2" x 2" Class 3, 4 receiver.

Hitch & Trailer Anti-theft Lock Kit

TSK1-AS for 17/8" & 2" couplers includes:

- TCL1-AS BLOCKHEAD Trailer Coupler Lock for unattended trailers; Fits 17/8" & 2" flat lip couplers (3³/4" max. width).
- RC1 Adjustable Trailer Coupler Latch Lock. Adjusts from 1/2" to 21/2" opening.
- RH3 Receiver Hitch Lock. 5/8" diameter. Fits all Class III and IV hitches.
- TSK3-AS for $2^{5}/_{16}$ " couplers includes:
- TCL3-AS BLOCKHEAD Trailer Coupler Lock for unattended trailers; Fits 2⁵/₁₆" flat lip couplers (4¹/₂" max width).
- RC1 Adjustable Trailer Coupler Latch Lock. Adjusts from 1/2'' to 21/2'' opening.
- RH3 Receiver Hitch Lock. 5/8" diameter. Fits all Class III and IV hitches.



Other Products

STL	Spare Tire Lock
	with 1/2" diameter pin. Adjusts from
	$\frac{1}{2}$ " to $\frac{7}{8}$ " opening (shown).
CAB	Cable Lock with 10" x 5/16" aircraft
	style cable and integral lock system.

- style cable and integral lock system. KPL King Pin Lock. Fits all king pin couplers.
- CRS Kit Any Dead Bolt Lock can be KEYED ALIKE quickly and limply with our exclulive CRS Kit. 50 keyed-alike corel. Two service keys. Works with all Dead Bolt brand products.



Keyed-Alike Hitch & Trailer Lock Sets

Set includes one hitch lock and one coupler lock KEYED ALIKE for your convenience. Now you can lock your hitch and trailer with one key! RHC22 For 11/4" x 11/4" Class 2 receiver hitch AND lever-style coupler requiring $a^{1}/2^{"}$ opening. For 11/4" x 11/4" Class 2 receiver RHC23 hitch AND lever-style coupler requiring a 2" opening. For 11/4" x 11/4" Class 2 receiver RHC24 hitch AND lever-style coupler requiring a $2^{1}/2^{"}$ opening. RHC32 For 2"x 2" Class 3 and 4 receiver hitch AND lever-style coupler requiring $a^{1/2}$ " opening (shown. RHC33 For 2" x 2" Class 3 and 4 receiver hitch AND lever-style coupler requiring a 2" openina. RHC34 For 2" x 2" Class 3 and 4 receiver hitch AND lever-style coupler requiring a $2^{1}/_{2}$ " opening. RHC3S For 2" x 2" Class 3 and 4 receiver hitch AND surge broke-style coupler requiring a $3\frac{3}{8}$ " opening. RHC36 For 2" x 2" receiver hitch (Class 3, 4) & coupler requiring 7/8" opening. RHC32-SS Stainless steel for 2" x 2" Class 3 and 4 receiver hitch AND lever-style coupler requiring a 1/2'' opening.

